

In the claims:

Cancel claims 2, 3 and 9 without prejudice.

Amend the following claims:

1. (Amended) A cover assembly for a cart, said cover assembly comprising:

- A10
- a) an enclosure including a hollow interior dimensioned to receive the cart therein when said enclosure is disposed in an operative position,
 - b) said enclosure including a top and a sidewall, said top disposed in overlying relation to an upper portion of the cart and said sidewall depending downwardly from said top in overlying, at least partially surrounding relation to a plurality of sides of the cart,
 - c) an access opening formed in said sidewall in aligned relation with a corresponding side of the cart,
 - d) a closure structure selectively positionable between a closed and an open position relative to said access opening,
 - e) said access opening disposed and dimensioned to access contents of the cart and allow passage of the contents therethrough, when said closure is in said open position,
 - f) said enclosure formed of a flexible, hypo-allergenic material selectively oriented in either said operative position or a collapsed stored position, and
 - g) a storage assembly including at least a first compartment

Q10
mounted within said hollow interior of said enclosure,
said first compartment disposed and structured to isolate
the contents thereof from the cart and a remainder of
said hollow interior of said enclosure.

Q11 4. (Amended) A cover assembly as recited in claim 1 wherein said
access opening is disposed in overlying alignment with at
least a majority of one side of the cart.

Q12 7. (Amended) A cover assembly as recited in claim 6 wherein said
drape is correspondingly dimensioned and configured to said
access opening and disposed in overlying, covering relation to
the one side of the cart when said closure structure is in
said closed position.

Q13 10. (Amended) A cover assembly as recited in claim 1 wherein said
storage assembly further comprises at least a second
compartment secured to an exterior of said wall assembly and
structured to removably contain contents removed from said
cart.

11. (Amended) A cover assembly as recited in claim 10 wherein said
storage assembly further comprises at least a third
compartment secured to an exterior of said enclosure and
including a window formed therein, said window disposed in
aligned relation with an interior of said third compartment to
facilitate viewing of the interior of said third compartment
there through.

Q14 20. (Amended) A cover assembly designed to be removably mounted on
a mobile cart, said cover assembly comprising:

- 9/14
- a) an enclosure including a hollow interior dimensioned to receive a cart therein when said enclosure is oriented in an operative position,
 - b) said enclosure including a top and a sidewall, said top disposed in overlying relation to an upper portion of said cart and said sidewall extending downwardly from said top in overlying, at least partially surrounding relation to a plurality of sides of the cart,
 - c) an access opening formed in said sidewall in aligned relation with a corresponding portion of the cart,
 - d) a closure structure selectively positionable between a closed position and an open position relative to said access opening,
 - e) said access opening disposed and dimensioned to access contents of the cart and allow passage of the contents therethrough when said closure is in said open position,
 - f) said enclosure including an open bottom disposed at a lower end of said sidewall and dimensioned to allow a bottom of the cart to pass therethrough,
 - g) a reinforcement assembly comprising a plurality of reinforced portions connected to said enclosure at a plurality of spaced apart locations,
 - h) said plurality of reinforced portions comprising a plurality of corner pads disposed in overlying, at least partially covering relation to corner portions of said top,

- GM
- i) said reinforcement portions further comprising an elongated peripheral seam extending continuously along an exterior of said enclosure contiguous to a commonly exposed peripheral junction between said side wall and said top, and
 - j) a storage assembly including at least one pocket mounted on an interior of said sidewall and structured to isolate the contents thereof from said cart when said enclosure is in said operative position.
-

Add the following claims:

21. A cover assembly as recited in claim 20 wherein said enclosure is formed of a flexible, hypo-allergenic material selectively oriented in either said operative position or a collapsed, stored position.
22. A cover assembly for a cart, said cover assembly comprising:
- GS
- a) an enclosure including a hollow interior dimensioned to receive the cart therein when said enclosure is disposed in an operative position,
 - b) said enclosure including a top and a sidewall, said top disposed in overlying relation to an upper portion of the cart and said sidewall depending downwardly from said top in overlying, at least partially surrounding relation to a plurality of sides of the cart,
 - c) an access opening formed in said sidewall in aligned relation with a corresponding side of the cart,

- AS
- d) a closure structure selectively positionable between a closed and an open position relative to said access opening, and
 - e) a storage assembly including at least a first compartment mounted within said hollow interior of said enclosure, said first compartment disposed and structured to isolate the contents thereof from the cart and a remainder of said hollow interior of said enclosure.

- 23. A cover assembly as recited in claim 22 wherein said enclosure is formed from a hypo-allergenic material.
 - 24. A cover assembly as recited in claim 22 wherein said storage assembly further comprises at least a second compartment secured to an exterior of said wall assembly and structured to removably contain contents removed from said cart.
-